



Physical Characteristics

Galaxy is made of industrial grade plastic. It is designed for rugged use and can withstand rough handling and shocks in field use. The dumbbell shape is slung on the shoulder to keep the hands free. It has an extra large belt hook equipped with a spring-loaded clip for secure holding to belt loops. The line cord is braided in superior yarn with angled bed of nails and piercing pin.

Galaxy

Craft Test Set

Technical Specifications

Electrical	
Current	< 90mA
Off-hook DC resistance	150 Ω
Off-hook AC impedance	600 Ω
Dialing	
Pulse rate	10PPS + 1 PPS
Break/Make ratio	60 / 40
Inter digit pause	720-880 ms
DTMF output	
High level	-8 + 2 dB
Low level	-6 + 2 dB
Twist	2 + 1 dB

Memory dialing	
Memory capacity	10 speed dial, one turret
Digit capacity	Each memory 23 digits max
Pause duration	3.6 Sec
Physical	
Dimension	9.1 x 2.9 x 3.7 inches
Weight	1.1 lbs
Water proof	Meets IP 41
Operation environment	
Environment temperature	-10°C ~ 55°C
Relative humidity	10% ~ 95%
Environment noise	≤ 60dB

Contact

Aines Mfg Corp.

Tel: 631-471-3900

e-mail: jkern@aines.com or hhepensteil@aines.com

website: www.aines.com

AINES
MANUFACTURING CORP.